



Features:

1. Short cylindrical center mounting.
2. The jaws for K11A,k11C and K11D chucks are composed of two-piece jaws.They can perform as either internal jaws through adjustment.
3. The jaws for K11A and K11D chucks conform to ISO3442 standard.
- 4.Model K11C chucks are supplied with traditional two-piece jaws.
5. We can provide all kinds of soft jaws.

- ✦ High precision ;Ü0.05mm.
- ✦ Flimsy parts are specifically engineered by quenching,for greater durability and extended life.
- ✦ High self-centring precision and superior gripping forde to meet precision machining demands.

Dimension parameters

Size	D1	D2	D3	H	H1	H2	h	Z-d	Max.input torque	r/min	Net.WT
------	----	----	----	---	----	----	---	-----	------------------	-------	--------

160A	130	142	40	109	65	71	5	3-M8	160	2500	8.3
200C	165	180	65	122	75	78	5	3-M10	250	2000	14.1
200A	165	180	65	122	75	80	5	3-M10	250	2000	14.1
240C	195	215	70	130	80	84	8	3-M12	320	1600	20
250C	206	226	80	130	80	84	5	3-M12	320	1600	23
250A	260	226	80	136	80	86	5	3-M12	320	1600	23
315A	260	285	100	153	90	95	6	3-M16	400	1200	41
320C	270	290	100	153.5	95	101.5	12	3-M16	400	1200	42
325C	272	296	100	154.5	96	102.5	12	3-M16	400	1200	44
325A	272	296	100	169.5	96	105.5	6	3-M16	400	1200	46
380C	272	350	135	156.5	98	104.5	6	3-M16	500	1000	60
380A	325	350	135	171.5	98	17.5	6	3-M16	500	1000	62
400D	340	368	130	172	100	108	6	3-M16	500	1000	71
500D	440	465	210	202	115	126	6	6-M16	630	800	117.6
500A	440	465	210	202	115	126	6	6-M16	630	800	119
630D	560	595	270	218	133.5	142	7	6-M16	800	600	-