



Features:

1. Short cylindrical center mounting.
2. The jaws for K11A, K11C and K11D chucks are composed of two-piece jaws. They can perform as either internal jaws through adjustment.
3. The jaws for K11A and K11D chucks conform to ISO3442 standard.
4. Model K11C chucks are supplied with traditional two-piece jaws.
5. We can provide all kinds of soft jaws.

✦ High precision $\pm 0.05\text{mm}$.

✦ Germany, Japan advanced machining technologies and machine equipments.

✦ International advanced heat treatment equipment.

✦ Have characteristics of high precision and high gripping force.

✦ More suitable for high precision processing.

Particular wrench design have more humanization.

Dimension parameters

Size	D1	D2	D3	H	H1	H2	h	Z-d	Max.input torque	Max.speed	Net.WT
80	55	66	16	66	50	-	3.5	3-M6	40	4000	1.9
100	72	84	22	74.5	55	-	3.5	3-M8	60	3500	3.2
125	95	108	30	84	58	-	4	3-M8	100	3000	5
130	100	115	30	86	60	-	3.5	3-M8	100	3000	5.6
160	130	142	40	95	65	-	5	3-M8	160	2500	8.8
165	130	145	40	96.5	66.5	-	4.5	3-M8	250	2500	9.5
190	155	172	55	105	75	-	5	3-M10	250	2000	13.8
200	165	180	65	109	75	-	5	3-M10	250	2000	15.5
240	195	215	70	120	80	-	8	3-M12	320	2000	24
250	206	226	80	120	80	-	5	3-M12	320	1600	25.7
315	260	285	100	147	90	-	6	3-M16	400	1200	47
320	270	290	100	152.5	95	-	11	3-M16	400	1200	47.5
325	272	296	100	153.5	96	-	12	3-M16	400	1200	49
380	325	350	135	155.7	98	-	6	3-M16	500	1000	65